GEP-7523



75" INTERACTIVE FLAT PANEL



















4k ULTRA HIGH DEFINATION



OPS Dual Operationg System

















4k ULTRA HIGH DEFINATION



20 POINT TOUCH



0PS



SPECIFICATIONS

PANEL	Size	Respond Time	Visual Ratio	Panel Type	Display Colours
	75"	8ms	16:9	CSOT	1.07B (10bit)
	Frequency	Max Visual Area	Resolution	Pixel Pitch	Colour Saturabilty
	60 Hz	1650(H)x928(V)mm	3840(H) x 2160(V)	0.4296 x 0.4296 mm	72%
	Brightness	Life Span	Contrast Ratio	Light Source	View Angle
	350cd/m2	≥50000hrs	50 0 0:1	DLED	178° (H/V)
AUDIO VIDEO	SPEAKEDS	Sound Track		Power	
PARAMETERS	SPEAKERS	2	.0 2 x 1		x 16W
TOUCH PARAMETERS	Touch Specifications		Support System		Output Coordinates
	Non-contact infrared sensing technology		Windows 10/ Windows 8/ Windows 7/ Windows XP/ Android/ Linux/ Mac OS X/ Chrome		32767(W) x 32767 (D)
	Touch Points	Min. Identifier	Writing Display		Writing Height
	20 Points touch	2 mm	Single Stylus Pen 2 Colour		≤3mm
	Respond Time	Touch Depth	Input Mode		
	≤5ms	±1mm	Opaque object (finger, Pen, etc)		-
SYSTEM	Version	СРИ	GPU	RAM	ROM
	Android 13	Quad Core A55 1.9 Ghz	Mali G52MP2	4GB System Memory	32GB System Storage
WIRELESS	BLUETOOTH	Version	Working Frequency	Working Distance	Remark Via
		5.2	2.4 GHz	Upto 10 mtrs.	WB800D.3 &WB663U
	WIFI	Version	Working Frequency	Working Distance	Remark Via
		802.11ac/b/g/n/a/ax	2.4 GHz/5GHz	Upto 10 mtrs.	WB800D.3 &WB663U.
REAR I/O INTERFACE	HDMI IN	USB 2.0	USB 3.0	USB Touch Port	Audio In
	2	1	1	1	1
	Line Out	Optical Out	VGA Input Port	RS 232	LAN RJ 45 In
	1	1	1	1	1
			MIC In		
			1		
FRONT INTERFACE	USB 3.0	Touch USB	HDMI I	Туре С	
	2	1	1	1 (USB Function Only)	
POWER	Voltage	Max. Power Consumption		Standby Power Consumption	
	100-240AC 50/60 Hz 3.5A	40	400W		≤0.5W
STRUCTURE	Bare Dimension	Packing Dimension	Machine + Wall I	Mount Thickness	VESA Hole Site
	1706.7x1044.4x117.6 mm	1860 x 220 x 1160mm	143.6mm		600 x 400mm
	Net Weight	Gross Weight	Wall Mounting Screw Specifications		
	52.2 Kg	61.6 Kg	M8 x 20mm		-
ENVIRONMENT	Working Temperature	Working Humidity	Storage Temperature	Storage Humidity	Working Elevation
	0°C~40°C	10%~90%RH	-20°C~60°C	10%~90%RH	<5000m
OPS	Processor Options	Generation Options	System Memory Options	RAM Options C	ertifications Options
	Intel® Core™ i3, i5 & i7	10th, 11th & 12th Gen	128GB to 2TB	4GB to 16GB CE,	FCC,ROHS, ISO 9001 : 2008, ISO 14001