GEP-6523



65" INTERACTIVE FLAT PANEL







































Note 5

4k ULTRA HIGH DEFINATION







SPECIFICATIONS

PANEL	Size	Respond Time	Visual Ratio	Panel Type	Display Colours	
	65"	8ms	16:9	CSOT	1.07B (10bit)	
	Frequency	Max Visual Area	Resolution	Pixel Pitch	Colour Saturabilty	
	60 Hz	1429(H)x804(V)mm	38 40(H) x 2160(V)	0.372 x 0.372 mm	n 72%	
	Brightness	Life Span	Contrast Ratio	Light Source	View Angle	
	350cd/m2	≥ 500 00hrs	4000:1	DLED	178° (H/V)	
AUDIO VIDEO		Soun	Sound Track		Power	
PARAMETERS	SPEAKERS	2.0		2 x 16W		
TOUCH PARAMETERS	Touch Specifications		Support System		Output Coordinates	
	Non-contact infrared sensing technology		Windows 10/ Windows 8/ Windows 7/ Windows XP/ Android/ Linux/ Mac OS X/ Chrome			
	Touch Points	Min. Identifier	Writing Display		Writing Height	
	20 Points touch	2 mm	Single Stylus Pen 2 Colour		≤3mm	
	Respond Time	Touch Depth	Input Mode			
	≤5ms	±1mm	Opaque object (finger, Pen, etc)		-	
SYSTEM	Version	CPU	GPU	RAM	ROM	
	Android 13	Quad Core A55 1.9 Ghz	Mali G52MP2	4GB System Memo	ory 32GB System Storage	
WIRELESS	BLUETOOTH	Version	Working Frequency	Working Distance	e Remark Via	
		5.2	2.4 GHz	Upto 10 mtrs.	WB800D.3 &WB663U.1	
	WIFI	Vers ion	Working Frequency	Working Distance	e Remark Via	
		802.11ac/b/g/n/a/ax	2.4 GHz/5GHz	Upto 10 mtrs.	WB800D.3 &WB663U.1	
REAR I/O INTERFACE	HDMI IN	USB 2.0	USB 3.0	USB Touch Port	Audio In	
	2	1	1	1	1	
	Line Out	Optical Out	VGA Input Port	RS 232	LAN RJ 45 In	
	1	1	1	1	1	
			MIC In			
			1			
FRONT INTERFACE	USB 3.0	Touch USB	HDMII	Туре С		
	2	1	1	1 (USB Function Only)		
POWER	Voltage	Max. Power Consumption		Standby Power Consumption		
	100-240AC 50/60 Hz 2.8A	35	50W		≤0.5W	
STRUCTURE	Bare Dimension	Packing Dimension	Machine + Wall I	Mount Thickness VESA Hole Site		
	1484.6x919.8x117.2 mm	1630 x 220 x 1050mm	147.2	2mm	500 x 400mm	
	Net Weight	Gross Weight	Wall Mounting Screw Specifications			
	38.8 Kg	45.8 Kg	M8 x 20mm		-	
ENVIRONMENT	Working Temperature	Working Humidity	Storage Temperature	Storage Humidity	y Working Elevation	
	0°C~40°C	10%~90%RH	-20°C~60°C	10%~90%RH	<5000m	
OPS	Processor Options	Generation Options	System Memory Options	RAM Options	Certifications Options	
	Intel® Core™ i3, i5 & i7	10th, 11th & 12th Gen	128GB to 2TB	4GB to 16GB	CE,FCC,ROHS, ISO 9001 : 2008, ISO 14001	