

With **Note 5**
Writing Software

ZERO BONDING


4K
ULTRAHD

 **Windows 11** +  **android 13**

DUAL OPERATING SYSTEM WITH OPS

Upgradable to **android 14**

3 YEAR WARRANTY

- **Android 13**
Operating System
- **4K**
ULTRAHD
- **OPS INCLUDED**
- **Available upto 4gb**
System Memory
- **Primary - 32GB**
- **OPS Dual**
Operation
System
- **Front Type**
C USB Port
- **Anti Finger**
Touch
- **Interchangeable**
OPS
- **Wireless Screen**
Sharing
upto 9 devices
- **Usb 3.0 x 3 ports**
In Front

SPECIFICATIONS

PANEL	Size	Respond Time		Visual Ratio	Panel Type	Display Colours
	75"	4ms		16:9	BOE/LG IPS Panel	1.07B (10bit)
	Frequency	Max Visual Area		Resolution	Pixel Pitch	Colour Saturability
	60 Hz	1649.66(H)x927.93(V)mm		3840(H) x 2160(V)	0.4296 x 0.4296 mm	72%
	Brightness	Life Span		Contrast Ratio	Light Source	View Angle
	400cd/m2	≥50000hrs		4000:1	DLED	178° (H/V)
AUDIO VIDEO PARAMETERS	SPEAKERS	Sound Track			Power	
		2.0			2 x 20W	
TOUCH PARAMETERS	Touch Specifications			Support System		Output Coordinates
	Non-contact infrared sensing technology			Windows 10/ Windows 8/ Windows 7/ Windows XP/ Android/ Linux/ Mac OS X/ Chrome		32767(W) x 32767 (D)
	Touch Points	Min. Identifier		Writing Display		Writing Height
	20 Points touch	2 mm		Single Stylus Pen 2 Colour		≤3mm
	Respond Time	Touch Depth		Input Mode		
	≤10ms	±1mm		Opaque object (finger, Pen, etc)		-
SYSTEM	Version	CPU		GPU	RAM	ROM
	Android 13	Quad Core A55 2.1 Ghz		Mali G52MP2	4GB System Memory	32GB System Storage
WIRELESS	BLUETOOTH	Version	Working Frequency		Working Distance	Remark Via
		5	2.4 GHz		Upto 10 mtrs.	Wireless Module S107B
	WIFI	Version	Working Frequency		Working Distance	Remark Via
		802.11ac/bg/n/a/x	2.4 GHz/5GHz		Upto 10 mtrs.	Wireless Module S107B
REAR I/O INTERFACE	HDMI IN	USB 2.0		USB 3.0	USB Touch Port	Audio In
	2	1		2	1	1
	Line Out	Optical Out		Display Port	VGA Input Port	HDMI Out
	1	1		1	1	1
	Type C Port	RS 232		LAN RF 45 Out	LAN RF 45 In	
	1 Full Function	1		1	1	-
FRONT INTERFACE	USB 3.0	Touch USB		HDMI I	Type C	
	2	1		1	1 (Full Function is Optional)	
POWER	Voltage	Max. Power Consumption			Standby Power Consumption	
	100-240AC 50/60 Hz 4A	320W			≤0.5W	
STRUCTURE	Bare Dimension	Packing Dimension		Machine + Wall Mount Thickness		VESA Hole Site
	1707 x 91.8 x 1022.7mm	1873 x 270 x 1197mm		118mm (WIB9060G)		800 x 400mm
	Net Weight	Gross Weight		Wall Mounting Screw Specifications		
	61.8 Kg	81.3 Kg		M8 x 25mm		-
ENVIRONMENT	Working Temperature	Working Humidity		Storage Temperature	Storage Humidity	Working Elevation
	0°C~40°C	10%~90%RH		-20°C~60°C	10%~90%RH	<5000m
OPS	Processor Options	Generation Options	System Memory Options		RAM Options	Certifications Options
	Intel® Core™ i3, i5 & i7	10th, 11th & 12th Gen	128GB to 2TB		4GB to 16GB	CE,FCC,ROHS, ISO 9001 : 2008, ISO 14001