




Android 13 Operating System



4K ULTRA HIGH DEFINITION



48 MP Camera




Available upto 8gb System Memory



Primary - 128GB



Wireless Screen Sharing upto 9 devices



Front Type C USB Port



Anti Finger Touch



Usb 3.0 x 3 ports In Front

SPECIFICATIONS

PANEL	Size	65"	Respond Time	4ms	Visual Ratio	16:9	Panel Type	BOE/LG IPS Panel	Display Colours	1.07B (10bit)		
	Frequency	60 Hz	Max Visual Area	1432(H) x 807(V)mm	Resolution	3840(H) x 2160(V)	Pixel Pitch	0.372 x 0.372 mm	Colour Saturability	72%		
	Brightness	400cd/m2	Life Span	≥50000hrs	Contrast Ratio	4000:1	Light Source	DLED	View Angle	178° (H/V)		
	AUDIO VIDEO PARAMETERS		SPEAKERS		Sound Track			Power				
					2.0			2 x 20W				
TOUCH PARAMETERS	Touch Specifications			Support System			Output Coordinates					
	Non-contact infrared sensing technology			Windows 10/ Windows 8/ Windows 7/ Windows XP/ Android/ Linux/ Mac OS X/ Chrome			32767(W) x 32767 (D)					
	Touch Points	20 Points touch	Min. Identifier	2 mm	Writing Display		Single Stylus Pen 2 Colour		Writing Height		≤3mm	
	Respond Time	≤10ms	Touch Depth	±1mm	Input Mode			Opaque object (finger, Pen, etc)			-	
SYSTEM	Version	Android 13	CPU	Quad Core A55 2.1 Ghz	GPU	Mali G52MP2	RAM	8GB System Memory	ROM	128 GB System Storage		
	CAMERA & MICROPHONE		Front Build In		Sensor Size							
		8 Array Microphone and 10 Mtr Pickup Distance		48MP Sensor for 12MP Tetra Bayer with 1/2 optics								
		Viewing Angle		D114.9 H102.1 V85.7 ± 3°		Video Format		MJPEG/H264/H265				
		RESOLUTION				15FPS@mjpg		30FPS@mjpg/h264/h265		10FPS @YUY2		30FPS @YUY2
		4000 x 3000		3840x2160, 2560x1440, 1920x1080, 1280x720		1280 x 720		640 x 480, 320 x 240				
		1024 x 768, 640 x 480, 640 x 360, 320 x 180										
WIRELESS	BLUETOOTH		Version	5	Working Frequency	2.4 GHz	Working Distance	Upto 10 mtrs.	Remark Via		Wireless Module S107B	
	WIFI		Version	802.11ac/bg/n/a/x	Working Frequency	2.4 GHz/5GHz	Working Distance	Upto 10 mtrs.	Remark Via		Wireless Module S107B	
REAR I/O INTERFACE	HDMI IN	2	USB 2.0	1	USB 3.0	2	USB Touch Port	1	Audio In		1	
	Line Out	1	Optical Out	1	Display Port	1	VGA Input Port	1	HDMI Out		1	
	Type C Port	1 Full Function	RS 232	1	LAN RJ 45 Out	1	LAN RJ 45 In	1			-	
	FRONT INTERFACE		USB 3.0	2	Touch USB	1	HDMI I	1	Type C	1	TF Card	
POWER	Voltage		Max. Power Consumption			Standby Power Consumption						
	100-240AC 50/60 Hz 4A		280W			≤0.5W						
STRUCTURE	Bare Dimension		Packing Dimension		Machine + Wall Mount Thickness			VESA Hole Site				
	1485 x 91.6 x 897.5mm		1653 x 235 x 1037mm		116.5mm (WIB9060G)			600 x 400mm				
	Net Weight		Gross Weight		Wall Mounting Screw Specifications							
		47.8 Kg		61.8 Kg		M8 x 25mm						
ENVIRONMENT	Working Temperature		Working Humidity		Storage Temperature		Storage Humidity		Working Elevation			
	0°C~40°C		10%~90%RH		-20°C~60°C		10%~90%RH		<5000m			