



Android 13 Operating System

4K ULTRA HIGH DEFINITION

OPS INCLUDED

Available upto 8gb System Memory

Primary - 128GB

OPS Dual Operating System

Front Type C USB Port

Anti Finger Touch

Interchangeable OPS

Wireless Screen Sharing upto 9 devices

Usb 3.0 x 3 ports In Front

SPECIFICATIONS

PANEL	Size	Respond Time	Visual Ratio	Panel Type	Display Colours
	86"	4ms	16:9	BOE/LG IPS Panel	1.07B (10bit)
	Frequency	Max Visual Area	Resolution	Pixel Pitch	Colour Saturability
	60 Hz	1895.04(H)x1065.96(V)mm	3840(H) x 2160(V)	0.4935 x 0.4935 mm	72%
	Brightness	Life Span	Contrast Ratio	Light Source	View Angle
	400cd/m2	≥50000hrs	4000:1	DLED	178° (H/V)
AUDIO VIDEO PARAMETERS	SPEAKERS	Sound Track		Power	
		2.0		2 x 20W	
TOUCH PARAMETERS	Touch Specifications		Support System		Output Coordinates
	Non-contact infrared sensing technology		Windows 10/ Windows 8/ Windows 7/ Windows XP/ Android/ Linux/ Mac OS X/ Chrome		32767(W) x 32767 (D)
	Touch Points	Min. Identifier	Writing Display		Writing Height
	20 Points touch	2 mm	Single Stylus Pen 2 Colour		≤3mm
	Respond Time	Touch Depth	Input Mode		
	≤10ms	±1mm	Opaque object (finger, Pen, etc)		-
SYSTEM	Version	CPU	GPU	RAM	ROM
	Android 13	Quad Core A55 2.1 Ghz	Mali G52MP2	8GB System Memory	128GB System Storage
WIRELESS	BLUETOOTH	Version	Working Frequency	Working Distance	Remark Via
		5	2.4 GHz	Upto 10 mtrs.	Wireless Module S107B
	WIFI	Version	Working Frequency	Working Distance	Remark Via
		802.11ac/bg/n/a/x	2.4 GHz/5GHz	Upto 10 mtrs.	Wireless Module S107B
REAR I/O INTERFACE	HDMI IN	USB 2.0	USB 3.0	USB Touch Port	Audio In
	2	1	2	1	1
	Line Out	Optical Out	Display Port	VGA Input Port	HDMI Out
	1	1	1	1	1
	Type C Port	RS 232	LAN RF 45 Out	LAN RF 45 In	
	1 Full Function	1	1	1	-
FRONT INTERFACE	USB 3.0	Touch USB	HDMI I	Type C	
	2	1	1	1 (Full Function is Optional)	
POWER	Voltage	Max. Power Consumption		Standby Power Consumption	
	100-240AC 50/60 Hz 4A	380W		≤0.5W	
STRUCTURE	Bare Dimension	Packing Dimension	Machine + Wall Mount Thickness		VESA Hole Site
	1953.4 x 92 x 1161.4mm	2135 x 270 x 1332mm	130mm (WIB9060G)		800 x 600mm
	Net Weight	Gross Weight	Wall Mounting Screw Specifications		
	74.4 Kg	95.3 Kg	M8 x 25mm		-
ENVIRONMENT	Working Temperature	Working Humidity	Storage Temperature	Storage Humidity	Working Elevation
	0°C~40°C	10%~90%RH	-20°C~60°C	10%~90%RH	<5000m
OPS	Processor Options	Generation Options	System Memory Options	RAM Options	Certifications Options
	Intel® Core™ i3, i5 & i7	10th, 11th & 12th Gen	128GB to 2TB	4GB to 16GB	CE,FCC,ROHS, ISO 9001 : 2008, ISO 14001