



- Android 13 Operating System**
- 4k ULTRA HIGH DEFINITION**
- Available upto 4gb System Memory**
- Primary - 32GB**
- Front Type C USB Port**
- Anti Finger Touch**
- Wireless Screen Sharing upto 9 devices**
- Usb 3.0 x 3 ports In Front**

SPECIFICATIONS

PANEL	Size	Respond Time	Visual Ratio	Panel Type	Display Colours
	65"	4ms	16:9	BOE/LG IPS Panel	1.07B (10bit)
	Frequency	Max Visual Area	Resolution	Pixel Pitch	Colour Saturabilty
	60 Hz	1432(H) x 807(V)mm	3840(H) x 2160(V)	0.372 x 0.372 mm	72%
	Brightness	Life Span	Contrast Ratio	Light Source	View Angle
400cd/m2	≥50000hrs	4000:1	DLED	178° (H/V)	
AUDIO VIDEO PARAMETERS	SPEAKERS	Sound Track		Power	
		2.0		2 x 20W	
TOUCH PARAMETERS	Touch Specifications		Support System		Output Coordinates
	Non-contact infrared sensing technology		Windows 10/ Windows 8/ Windows 7/ Windows XP/ Android/ Linux/ Mac OS X/ Chrome		32767(W) x 32767 (D)
	Touch Points	Min. Identifier	Writing Display		Writing Height
	20 Points touch	2 mm	Single Stylus Pen 2 Colour		≤3mm
	Respond Time	Touch Depth	Input Mode		
≤10ms	±1mm	Opaque object (finger, Pen, etc)		-	
SYSTEM	Version	CPU	GPU	RAM	ROM
	Android 13	Quad Core A55 2.1 Ghz	Mali G52MP2	4GB System Memory	32GB System Storage
WIRELESS	BLUETOOTH	Version	Working Frequency	Working Distance	Remark Via
		5	2.4 GHz	Upto 10 mtrs.	Wireless Module S107B
	WIFI	Version	Working Frequency	Working Distance	Remark Via
		802.11ac/bg/n/a/x	2.4 GHz/5GHz	Upto 10 mtrs.	Wireless Module S107B
REAR I/O INTERFACE	HDMI IN	USB 2.0	USB 3.0	USB Touch Port	Audio In
	2	1	2	1	1
	Line Out	Optical Out	Display Port	VGA Input Port	HDMI Out
	1	1	1	1	1
	Type C Port	RS 232	LAN RJ 45 Out	LAN RJ 45 In	
1 Full Function	1	1	1	-	
FRONT INTERFACE	USB 3.0	Touch USB	HDMI I	Type C	
	2	1	1	1 (Full Function is Optional)	
POWER	Voltage	Max. Power Consumption		Standby Power Consumption	
	100-240AC 50/60 Hz 4A	280W		≤0.5W	
STRUCTURE	Bare Dimension	Packing Dimension	Machine + Wall Mount Thickness		VESA Hole Site
	1485 x 91.6 x 897.5mm	1653 x 235 x 1037mm	116.5mm (WIB9060G)		600 x 400mm
	Net Weight	Gross Weight	Wall Mounting Screw Specifications		
	47.8 Kg	61.8 Kg	M8 x 25mm		-
ENVIRONMENT	Working Temperature	Working Humidity	Storage Temperature	Storage Humidity	Working Elevation
	0°C~40°C	10%~90%RH	-20°C~60°C	10%~90%RH	<5000m