

With **Note 5**
Writing Software

ZERO BONDING

4K
ULTRAHD

 **Windows 11** +  **android 13**

DUAL OPERATING SYSTEM WITH OPS

Upgradable to **android 14**

3 YEAR WARRANTY

**Android 13**
Operating System

**4k ULTRA HIGH**
DEFINATION

**OPS INCLUDED**


**Available upto 8gb**
System Memory

**Primary - 128GB**

**OPS Dual**
Operation
System

**Front Type**
C USB Port

**Anti Finger**
Touch

**Interchangeable**
OPS

**Wireless Screen**
Sharing
upto 9 devices

**Usb 3.0 x 3 ports**
In Front

SPECIFICATIONS

PANEL	Size	Respond Time	Visual Ratio	Panel Type	Display Colours
	110"	8ms	16:9	LG/BOE	1.07B (10bit)
	Frequency	Max Visual Area	Resolution	Pixel Pitch	Colour Saturability
	60 Hz	2439(H)x1374(V)mm	3840(H) x 2160(V)	0.6345 x 0.6345 mm	72%
	Brightness	Life Span	Contrast Ratio	Light Source	View Angle
	400cd/m2	≥30000hrs	1200:1	DLED	178° (H/V)
AUDIO VIDEO PARAMETERS	SPEAKERS	Sound Track		Power	
		2.0		2 x 20W	
TOUCH PARAMETERS	Touch Specifications		Support System		Output Coordinates
	Non-contact infrared sensing technology		Windows 10/ Windows 8/ Windows 7/ Windows XP/ Android/ Linux/ Mac OS X/ Chrome		32767(W) x 32767 (D)
	Touch Points	Min. Identifier	Writing Display		Writing Height
	20 Points touch	2 mm	Single Stylus Pen 2 Colour		≤3mm
	Respond Time	Touch Depth	Input Mode		
		≤10ms	Opaque object (finger, Pen, etc)		-
SYSTEM	Version	CPU	GPU	RAM	ROM
	Android 13	Quad Core A55 2.1 Ghz	Mali G52MP2	8GB System Memory	128GB System Storage
WIRELESS	BLUETOOTH	Version	Working Frequency	Working Distance	Remark Via
		5	2.4 GHz	Upto 10 mtrs.	Wireless Module S107B
	WIFI	Version	Working Frequency	Working Distance	Remark Via
		802.11ac/bg/n/a/x	2.4 GHz/5GHz	Upto 10 mtrs.	Wireless Module S107B
REAR I/O INTERFACE	HDMI IN	USB 2.0	USB 3.0	USB Touch Port	Audio In
	2	1	2	1	1
	Line Out	Optical Out	Display Port	VGA Input Port	HDMI Out
	1	1	1	1	1
	Type C Port	RS 232	LAN RF 45 Out	LAN RF 45 In	Type C
		1 Full Function	1	1	1
FRONT INTERFACE	USB 3.0	Touch USB	HDMI I	Type C	
	2	1	1	1 (Full Function is Optional)	
POWER	Voltage	Max. Power Consumption		Standby Power Consumption	
	100-240AC 50/60 Hz 4A	720W		≤0.5W	
STRUCTURE	Bare Dimension	Packing Dimension	Machine + Wall Mount Thickness		VESA Hole Site
	2501.2 x 103 x 1478mm	2764 x 260 x 1675mm	130mm (WIB9060G)		1000 x 400mm
	Net Weight	Gross Weight	Wall Mounting Screw Specifications		
	167 Kg	188 Kg	M8 x 25mm		-
ENVIRONMENT	Working Temperature	Working Humidity	Storage Temperature	Storage Humidity	Working Elevation
	0°C~40°C	10%~90%RH	-20°C~60°C	10%~90%RH	<5000m
OPS	Processor Options	Generation Options	System Memory Options	RAM Options	Certifications Options
	Intel® Core™ i3, i5 & i7	10th, 11th & 12th Gen	128GB to 2TB	4GB to 16GB	CE,FCC,ROHS, ISO 9001 : 2008, ISO 14001