


# CE65FB

(8GB System Memory / 64GB Storage) Optional



## 65" INTERACTIVE FLAT PANEL

# Bytello



### Bytello Class



### Bytello DMS



### Bytello Share



#### Bytello Class

##### Teach anytime anywhere.

Cloud-based lesson preparation for teachers accessing and sharing lesson plans with one another at anytime and anywhere.



#### Bytello DMS

##### The classroom companion for IT Teams

Bytello DMS makes it easy to set up program operation schedules to automate and simplify IT operations. IT team can also monitor the usage status of equipment and access data for continuous optimization and reporting.



#### Bytello Share

##### Teach your students to Bytello Share.

Secure two-way screen sharing for up to 9 students simultaneously while compatible with all major screen-sharing protocols, including Miracast, Airplay, and Chromecast.



HDMI Out



4k ULTRA HIGH  
DEFINATION



OPS DUAL  
OPERATING  
SYSTEM



INTERCHANGABLE  
OPS



OPS INCLUDED

## Product Specifications

| PANEL                     | Size                                    | Respond Time          | Visual Ratio                                                                   | Panel Type                    | Display Colours                         |
|---------------------------|-----------------------------------------|-----------------------|--------------------------------------------------------------------------------|-------------------------------|-----------------------------------------|
|                           | 65"                                     | 6.5ms                 | 16:9                                                                           | VA                            | 1.07B (10bit)                           |
|                           | Frequency                               | Max Visual Area       | Resolution                                                                     | Pixel Pitch                   | Colour Saturability                     |
|                           | 60 Hz                                   | 1428(H) x 803(V)mm    | 3840(H) x 2160(V)                                                              | 0.372 x 0.372 mm              | 72%                                     |
|                           | Brightness                              | Life Span             | Contrast Ratio                                                                 | Light Source                  | View Angle                              |
|                           | 350cd/m2                                | ≥30000hrs             | 5000:1                                                                         | DLED                          | 178° (H/V)                              |
| AUDIO VIDEO<br>PARAMETERS | SPEAKERS                                | Sound Track           |                                                                                | Power                         |                                         |
|                           |                                         | 2.0                   |                                                                                | 2 x 16W 89db                  |                                         |
| TOUCH PARAMETERS          | Touch Specifications                    |                       | Support System                                                                 |                               | Output Coordinates                      |
|                           | Non-contact infrared sensing technology |                       | Windows 10/ Windows 8/ Windows 7/ Windows XP/ Android/ Linux/ Mac OS X/ Chrome |                               | 32768(W) x 32768 (D)                    |
|                           | Touch Points                            | Min. Identifier       | Writing Display                                                                |                               | Writing Height                          |
|                           | 40 Points touch                         | 3 mm                  | Passive Infrared Pen                                                           |                               | ≤3mm                                    |
|                           | Respond Time                            | Touch Depth           | Input Mode                                                                     |                               |                                         |
|                           | ≤10ms                                   | ±1mm                  | Opaque Object (finger, Pen, etc)                                               |                               | -                                       |
| SYSTEM                    | Version                                 | CPU                   | GPU                                                                            | RAM                           | ROM                                     |
|                           | Android 13                              | A55 x 4               | Mali G52MP2                                                                    | 4GB/ (8GB Optional)           | 32GB/(64GB Optional)                    |
| WIRELESS                  | BLUETOOTH                               | Version               | Working Frequency                                                              | Working Distance              | Remark Via                              |
|                           |                                         | 5                     | 2.4 GHz                                                                        | Upto 10 mtrs.                 | Wireless Module S107B                   |
|                           | WIFI                                    | Version               | Working Frequency                                                              | Working Distance              | Remark Via                              |
|                           |                                         | 802.11ac/bg/n/a/x     | 2.4 GHz/5GHz                                                                   | Upto 10 mtrs.                 | Wireless Module S107B                   |
| REAR I/O INTERFACE        | HDMI IN                                 | USB 2.0               | USB 3.0                                                                        | USB Touch Port                | Audio In                                |
|                           | 3                                       | 1                     | 4                                                                              | 2                             | 1                                       |
|                           | Audio Out                               | SPDIF                 | Display Port                                                                   | VGA Input Port                | HDMI Out                                |
|                           | 1                                       | 1                     | 1                                                                              | 1                             | 1                                       |
|                           | Type C Port                             | RS 232                | LAN RJ 45 Out                                                                  | LAN RJ 45 In                  |                                         |
|                           | 1 Full Function                         | 1                     | 1                                                                              | 1                             | -                                       |
| FRONT INTERFACE           | USB 3.0                                 | Touch USB             | HDMI I                                                                         | Type C                        |                                         |
|                           | 2                                       | 1                     | 1                                                                              | 1 (Full Function is Optional) |                                         |
| POWER                     | Voltage                                 | Max. Power            | Max. Power w OPS                                                               | Standby Power Consumption     |                                         |
|                           | 100-240AC 50/60 Hz 4A                   | 200W                  | 360W                                                                           | ≤0.5W                         |                                         |
| STRUCTURE                 | Bare Dimension                          | Packing Dimension     | Machine + Wall Mount Thickness                                                 |                               | VESA Hole Site                          |
|                           | 1488.4 x 896.6 x 87.2mm                 | 1628 x 208 x 1005mm   | 117.2mm (WIB9060G)                                                             |                               | 600 x 400mm                             |
|                           | Net Weight                              | Gross Weight          | Wall Mounting Screw Specifications                                             |                               |                                         |
|                           | 34.3 Kg                                 | 44.75 Kg              | M8 x 25mm                                                                      |                               | -                                       |
| ENVIRONMENT               | Working Temperature                     | Working Humidity      | Storage Temperature                                                            | Storage Humidity              | Working Elevation                       |
|                           | 0°C~40°C                                | 10%~90%RH             | -20°C~60°C                                                                     | 10%~90%RH                     | <5000m                                  |
| OPS                       | Processor Options                       | Generation Options    | System Memory Options                                                          | RAM Options                   | Certifications Options                  |
|                           | Intel® Core™ i3, i5 & i7                | 10th, 11th & 12th Gen | 128GB to 2TB                                                                   | 4GB to 16GB                   | CE,FCC,ROHS, ISO 9001 : 2008, ISO 14001 |

