Rooms Controller

RT10

Android | 10.1" | IPS Touch Screen | PoE-Powered | Software Pre-install

A remote meeting controller designed exclusively for enterprise video conferencing management. Preloaded with popular video conferencing software controls, simply pair it to initiate, join, manage, and conclude meetings, along with screen sharing and more. No more need for constant device handling – it significantly enhances meeting efficiency.





VooV Meeting Rooms



Lark Rooms



Zoom Rooms

FEATURES

ANDROID TOUCHSCREEN DISPLAY

With the Android operating system, it's easy to get started. Featuring a spacious 10.1-inch capacitive touchscreen that supports multi-touch, providing a convenient and smooth user experience.

ONE-CLICK MEETING CONTROL

Pre-installed with popular meeting applications like Zoom,VooV Meeting, Lark, and more, making it a breeze to manage your video conferences with just one click.

ADJUSTABLE VIEWING ANGLE

Equipped with a built-in multi-angle adjustable stand, ensuring a clear view of the screen from various seating positions.

VERSATILE POWER OPTIONS

Easily power the device through USB and PoE interfaces for added convenience.

SPECIFICATIONS

HARDWARE PLATFORM

Operating System	Android 9.0
CPU	Amlogic A311d, 4xCortex-A73+2xCoretex-A53
GPU	ARM G52 MP4(6EE),OpenGL ES 3.2, Vulkan 1.1 , OpenCL 2.0
Storage	4G RAM+16GB ROM
Codec	**Encoder:**H.264/H.265 1 x 1080P@60fps **Decoder:** VP9 Profile-2 up to 4Kx2K@60fps H.265 HEVC MP-10@L5.1 up to 4Kx2K@60fps AVS2-P2 Profile up to 4Kx2K@60fps H.264 AVC HP@L5.1 up to 4Kx2K@30fps H.264 MVC up to 1080P@60fps
Wi-Fi	IEEE802.11a/b/g/n/ac,WPA,WPA2
Bluetooth	BT 5.0

VIDEO SPECIFICATIONS AND FEATURES

Touch Screen	10.1-inch IPS touch screen,Multi-Touch
	Resolution: 1920×1200 (1280×800 optional)
	Visual Angle: 170 degrees
	Brightness: 300cd/㎡(typ)

INTERFACES

USB Interface	1 x USB2.0 Type-C (device) ; 1x USB 2.0 Type-A
Network Interface	1 x RJ45: 10/100/1000 Base-T 1 x 2.4G/5G WiFi5

PHYSICAL CHARACTERISTICS

Dimensions	243mm (W) × 164mm (D) × 33mm (H)
WIFI Frequency	2.4G&5G Dual frequency
Micphone	Pickup range of 2 meters
Speaker	1 × 1.5W
Environmental Specification	**Operating temperature:** 0°C to 40°C **Operating humidity:** 10% to 80% **Non-Operating temperature:** -40° to -70°C **Non-Operating humidity (non-condensing):** 0% to 95%
Approval and Compliance	CQC RoHS



INTERFACE

1 —— Power Jack
2 —— LAN (PoE Support)
3 —— LOCK
4 —— USB 2.0

