65" INTERACTIVE FLAT PANEL







Available upto 8gb System Memory



Primary - 128GB



OPS INCLUDED



Interchangable OPS





Front Type C USB Port



4k ULTRA HIGH DEFINATION



OPS Dual Operationg System

With 3 years warranty

Specifications

















40 POINT TOUCH

Front Type C USB Port









PANEL	Size	Respond Time	Backlight Type	View Angle	Display Colours
	65"	8ms	DLED	178° (H/V)	1.07B (8 bit+FRC)
	Frequency	Max Visual Area	Resolution	Pixel Pitch	Colour Gamut(x% NTS
	60 Hz	1428.48(H)x803.52(V)mm	3840(H) x 2160(V)	0.3720 x 0.3720 mm	72%
	Brightness	Life Span	Contrast Ratio		
	400cd/m2	≥30,000hrs	1200:1	-	-
AUDIO VIDEO		Sound Track		Power	
PARAMETERS SPEAKERS		2.0		2 x 15W/8ohm	
TOUCH PARAMETERS	Touch Specifications		Support System		Interpolation Res.
	Infrared sensing technology		Windows11/ 10/ 8/ 7/ XP/ Android/ Linux/ Mac OS X/ Chrome		32768(W) x 32768 (D
	Touch Points	Min. Identifier	Writing	Display	Power Consumption
	40 Points touch	2.0 mm	Single Stylus Pen 2 Colour		≤2w
	Respond Time	Touch Accuracy	Output Mode		Surface Protection
	≤5ms	90% ±1mm	HID Standard		3.2mm Toughened Gla
SYSTEM	Version	СРИ	GPU	RAM	ROM
	Android 13	Quad Core A55 1.8 Ghz	Mali G52MP2	8GB DDR4	128GB
WIRELESS	BLUETOOTH	Version	Working Frequency	Working Distance	Remark Via
		5	2.1 GHz	Upto 10 mtrs.	Mediatek MT7663BL
	WIFI	Version	Working Frequency	Working Distance	Remark Via
		802.11 a/b/g/n/ac	2.4 GHz/5GHz	Upto 10 mtrs.	Mediatek MT7663BU
REAR I/O INTERFACE	HDMI IN	USB 2.0	USB 3.0	USB Touch Port	Audio In
	2	1	2	1	1
	Line Out	Optical Out	SPDIF Out	DP In	HDMI Out
	1	1	1	1 Optional	1 (Optional)
	Type C Port	RS 232	LAN 10/100/1000 Base T	LAN RJ 45	
	1 Full Function	1	1	1	-
FRONT INTERFACE	USB 3.0	Touch USB	HDMI IN	т	ype C
	2	1	1	1 (Full Function is Optional)	
POWER	Voltage	Power Consun	nption w/o OPS OPS Power		Standby Power
	200-240AC 50/60 Hz	22	ow	DC 18V/5A	≤0.5W
STRUCTURE	Bare Dimension	Packing Dimension	Housing	Material	VESA Hole Site
	1482.1 x 87.7 x 897.4mm	1640 x 185 x 1010mm	Aluminium/ Metal Plate Black		600 x 400mm
	Net Weight	Gross Weight	Wall Mounting Screw Specifications		
			M8 x 25mm		
ENVIRONMENT	Working Temperature	Working Humidity	Storage Temperature	Storage Humidity	Working Elevation
	0°C~40°C	10%~60%RH	-10°C~60°C	10%~80%RH	<5000m
OPS	Processor Options	Generation Options	System Memory Options RAM Options Certifications Options		
	Intel® Core™ i3, i5 & i7	10th, 11th & 12th Gen	128GB to 2TB	4GB to 16GB CE,F	CC,ROHS, ISO 9001 : 2008, ISO 14001