



Android 13
Operating System

4k ULTRA HIGH
DEFINATION

48 MP
Camera

Available upto 8gb
System Memory

Primary - 128GB

Wireless Screen
Sharing
upto 9 devices

USB 3.0
x 3 ports
In Front

Front Type
C USB Port

Anti Finger
Touch

OPS INCLUDED

OPS Dual
Operationg
System

Interchangable OPS

SPECIFICATIONS

| | | | | | |
|------------------------|---|---|--|---------------------------|---|
| PANEL | Size | Respond Time | Visual Ratio | Panel Type | Display Colours |
| | 75" | 4ms | 16:9 | BOE/LG IPS Panel | 1.07B (10bit) |
| | Frequency | Max Visual Area | Resolution | Pixel Pitch | Colour Saturability |
| | 60 Hz | 1649.66(H)x927.93(V)mm | 3840(H) x 2160(V) | 0.4296 x 0.4296 mm | 72% |
| | Brightness | Life Span | Contrast Ratio | Light Source | View Angle |
| | 400cd/m2 | ≥50000hrs | 4000:1 | DLED | 178° (H/V) |
| AUDIO VIDEO PARAMETERS | SPEAKERS | Sound Track | | Power | |
| | | 2.0 | | 2 x 20W | |
| TOUCH PARAMETERS | Touch Specifications | | Support System | | Output Coordinates |
| | Non-contact infrared sensing technology | | Windows 10/ Windows 8/ Windows 7/ Windows XP/ Android/ Linux/ Mac OS X/ Chrome | | 32767(W) x 32767 (D) |
| | Touch Points | Min. Identifier | Writing Display | | Writing Height |
| | 20 Points touch | 2 mm | Single Stylus Pen 2 Colour | | ≤3mm |
| | Respond Time | Touch Depth | Input Mode | | |
| | ≤10ms | ±1mm | Opaque object (finger, Pen, etc) | | - |
| SYSTEM | Version | CPU | GPU | RAM | ROM |
| | Android 13 | Quad Core A55 2.1 Ghz | Mali G52MP2 | 8GB System Memory | 128GB System Storage |
| CAMERA & MICROPHONE | Front Build In | | Sensor Size | | |
| | 8 Array Microphone and 10 Mtr Pickup Distance | | 48MP Sensor for 12MP Tetra Bayer with 1/2 optics | | |
| | Viewing Angle | | Video Format | | |
| | D114.9 H102.1 V85.7 ± 3° | | MJPG/H264/H265 | | - |
| | RESOLUTION | | | | |
| | 15FPS@mjpg | 30FPS@mjpg/h264/h265 | | 10FPS @YUY2 | 30FPS @YUY2 |
| | 4000 x 3000 | 3840x2160, 2560x1440, 1920x1080, 1280x720 | | 1280 x 720 | 640 x 480, 320 x 240 |
| | | 1024 x 768, 640 x 480, 640 x 360, 320 x 180 | | - | - |
| WIRELESS | BLUETOOTH | Version | Working Frequency | Working Distance | Remark Via |
| | | 5 | 2.4 GHz | Upto 10 mtrs. | Wireless Module S107B |
| | WIFI | Version | Working Frequency | Working Distance | Remark Via |
| | | 802.11ac/bg/n/a/x | 2.4 GHz/5GHz | Upto 10 mtrs. | Wireless Module S107B |
| REAR I/O INTERFACE | HDMI IN | USB 2.0 | USB 3.0 | USB Touch Port | Audio In |
| | 2 | 1 | 2 | 1 | 1 |
| | Line Out | Optical Out | Display Port | VGA Input Port | HDMI Out |
| | 1 | 1 | 1 | 1 | 1 |
| | Type C Port | RS 232 | LAN RJ 45 Out | LAN RJ 45 In | |
| | 1 Full Function | 1 | 1 | 1 | - |
| FRONT INTERFACE | USB 3.0 | Touch USB | HDMI I | Type C | TF Card |
| | 2 | 1 | 1 | 1 | 1 |
| POWER | Voltage | Max. Power Consumption | | Standby Power Consumption | |
| | 100-240AC 50/60 Hz 4A | 320W | | ≤0.5W | |
| STRUCTURE | Bare Dimension | Packing Dimension | Machine + Wall Mount Thickness | | VESA Hole Site |
| | 1707 x 91.8 x 1022.7mm | 1873 x 270 x 1197mm | 118mm (WIB9060G) | | 800 x 400mm |
| | Net Weight | Gross Weight | Wall Mounting Screw Specifications | | |
| | 61.8 Kg | 81.3 Kg | M8 x 25mm | | - |
| ENVIRONMENT | Working Temperature | Working Humidity | Storage Temperature | Storage Humidity | Working Elevation |
| | 0°C~40°C | 10%~90%RH | -20°C~60°C | 10%~90%RH | <5000m |
| OPS | Processor Options | Generation Options | System Memory Options | RAM Options | Certifications Options |
| | Intel® Core™ i3, i5 & i7 | 10th, 11th & 12th Gen | 128GB to 2TB | 4GB to 16GB | CE,FCC,ROHS, ISO 9001 : 2008, ISO 14001 |