CE75FB

(8GB System Memory / 64GB Storage) Optional



75" INTERACTIVE FLAT PANEL Bytello









Bytello Class

Teach anytime anywhere.

Cloud-based lesson preparation for teachers accessing and sharing lesson plans with one another at anytime and anywhere.



Bytello Share

Teach your students to Bytello Share.

Secure two-way screen sharing for up to 9 students simultaneously while compatible with all major screen-sharing protocols, including Miracast, Airplay, and Chromecast.



Bytello DMS

The classroom companion for IT Teams

Bytello DMS makes it easy to set up program operation schedules to automate and simplyfy IT operations. IT team can also monitor the usage status of equipment and access data for continuous optimization and reporting.



















Product Specifications

PANEL	Size	Respond Time	Visual Ratio	Panel Type	Display Colours
	75"	6.5ms	16:9	VA	1.07B (10bit)
	Frequency	Max Visual Area	Resolution	Pixel Pitch	Colour Saturabilty
	60 Hz	650.24(H) x 928.26(V)m	n 3840(H) x 2160(V)	0.372 x 0.372 mm	72%
	Brightness	Life Span	Contrast Ratio	Light Source	View Angle
	350cd/m2	≥30000hrs	5000:1	DLED	178° (H/V)
AUDIO VIDEO	CDEALIERO	Soun	nd Track	Power 2 x 16W 89db	
PARAMETERS	SPEAKERS		2.0		
TOUCH PARAMETERS	Touch Specifications		Support System		Output Coordinates
	Non-contact infrared sensing technology		Windows 10/ Windows 8/ Windows 7/ Windows XP/ Android/ Linux/ Mac OS X/ Chrome		
	Touch Points	Min. Identifier	Writing Display		Writing Height
	40 Points touch	3 mm	Passive Infrared Pen		≤3mm
	Respond Time	Touch Depth	Input Mode		
	≤10ms	±1.5mm	Opaque Object (finger, Pen, etc)		-
SYSTEM	Version	CPU	GPU	RAM	ROM
	Android 13	A55 x 4	Mali G52MP2	4GB/ (8GB Optional) 32GB/(64GB Optional
WIRELESS	BLUETOOTH	Version	Working Frequency	Working Distance	Remark Via
		5	2.4 GHz	Upto 10 mtrs.	Wireless Module S107
	WIFI	Version	Working Frequency	Working Distance	Remark Via
		802.11ac/bg/n/a/x	2.4 GHz/5GHz	Upto 10 mtrs.	Wireless Module S107
REAR I/O INTERFACE	HDMI IN	USB 2.0	USB 3.0	USB Touch Port	Audio In
	3	1	4	2	1
	Audio Out	SPDIF	Display Port	VGA Input Port	HDMI Out
	1	1	1	1	1
	Type C Port	RS 232	LAN RJ 45 Out	LAN RJ 45 In	
	1 Full Function	1	1	1	-
FRONT INTERFACE	USB 3.0	Touch USB	HDMI I	Type C	
	2	1	1	1 (Full Function is Optional)	
POWER	Voltage	Max. Power	Max. Power w OPS	Standby Power Consumption	
	100-240AC 50/60 Hz 4A	200W	360W	≤0.5W	
STRUCTURE	Bare Dimension	Packing Dimension	Machine + Wall Mount Thickness VESA Hole Site		
	1709 x 1020 x 88mm	1863 x 225 x 1140mm	118mm (V	VIB9060G)	800 x 400mm
	Net Weight	Gross Weight	Wall Mounting Screw Specifications		
	47.30 Kg	60.75 Kg	M8 x 25mm		-
ENVIRONMENT	Working Temperature	Working Humidity	Storage Temperature	Storage Humidity	Working Elevation
	0°C~40°C	10%~90%RH	-20°C~60°C	10%~90%RH	<5000m
OPS	Processor Options	Generation Options	System Memory Options	RAM Options Certifications Options	
	Intel® Core™ i3, i5 & i7	10th, 11th & 12th Gen	128GB to 2TB	4GB to 16GB CE	E,FCC,ROHS, ISO 9001 : 2008, ISO 14001





